

CLAIMS

1. Method of communication on an uplink between a user equipment (14a) and a first radio network controller (12a, 15a) of a cellular network infrastructure comprising an active set of base nodes (13, 17) which each
5 receive radio signals transmitted by the said user equipment, characterized in that it comprises the following actions:

- generation, in each base node of the active set, of at least a first frame of soft bits on the basis of the received radio signal and a corresponding first frame of hard bits;

10 - transmission in the cellular network infrastructure, from each base node of the active set, of an accuracy indicator which results from an error check on the frame of hard bits;

- transmission, to the first radio network controller, of the said first frame of hard bits from a base node (12a, 15a) whose accuracy indicator has a so-called "good" level, if at least one accuracy indicator has the said good
15 level;

- transmission, to the first radio network controller (12a, 15a) if no accuracy indicator has the said good level, of each of the first frames of soft bits from at least two base nodes and the combination in the first radio
20 network controller of the transmitted frames of soft bits in order to generate a second frame of hard bits.

2. Method of communication on an uplink according to Claim 1, characterized in that:

- each accuracy indicator transmitted in the cellular network
25 infrastructure for the said uplink is transmitted to the first radio network controller (12a);

- the said first radio network controller (12a), if it receives at least one accuracy indicator of good level, chooses that one of the base nodes whose accuracy indicator has the good level and requests the chosen base node to
30 transmit to it the said first frame of hard bits;

- the said first radio network controller, if it does not receive any accuracy indicator of good level, chooses at least two base nodes and requests them to transmit to it their frames of soft bits.

SUB
A1

5 4. Method of communication on an uplink according to Claim 2,
characterized in that, among the nodes whose accuracy indicator has the
good level, the first radio network controller chooses the one that meets
filtering criteria.

10
SUB
A1

- 15 - choosing, in the said first radio network controller (12a), at least two base nodes with the best quality indicators received and requesting the chosen base nodes to transmit, to the said first radio network controller, the frames of soft bits from each chosen base node.

- each accuracy indicator transmitted from another base node (17a, 17b, 17c) in the cellular network infrastructure for the said uplink, is transmitted to at least one base node (17a, 17b, 17c) of the said active set;

- each base node (17a, 17b, 17c) applies rules established between the base nodes to the quality indicators that it receives and transmits, in order to decide to transmit or not to transmit, to the said first radio network controller (15a), the first frame of hard bits from that base node or the first frame of soft bits, in order that that one of the first frames of hard bits whose accuracy indicator has a said good level is transmitted from a base node or that the frames of soft bits are transmitted from at least two base nodes in the absence of an accuracy indicator with the said good level.

7. Method of communication on an uplink according to Claim 1 or 2, characterized in that:

- at least one accuracy indicator transmitted in the cellular network infrastructure is transmitted to a second radio network controller;

- the said second radio network controller, if it receives an accuracy indicator with good level, transmits this accuracy indicator of good level to the first radio network controller, chooses that one of the base nodes whose accuracy indicator has the good level, transmits the accuracy indicator of good level to the first radio network controller and requests the chosen base node to send to it the said first frame of hard bits to provide for a transmission to the first radio network controller;

- the said radio network controller, if it does not receive an accuracy indicator of good level, chooses at least one base node and requests it to send to it its frame of soft bits to provide for a transmission to the first radio network controller.

8. Method of communication on an uplink according to one of the preceding claims, characterized in that it furthermore comprises the following actions executed in a base node comprising a base controller and grouping several base stations:

- generation, in at least one base station of the base node, of a third frame of soft bits on the basis of the radio signal received from the user equipment by the said base station for the said uplink and a third frame of hard bits;

- transmission in the base node, from each base station receiving the radio signal for the said uplink, of a local accuracy indicator that results from an error check on the frame of hard bits;

- transmission, to the base controller, of the third frame of hard bits from a base station whose local accuracy indicator has the said good level, if at least one local accuracy indicator has the said good level;

- transmission, to the base controller, if no local accuracy indicator has the said good level, of the frame of soft bits from at least one base station and combination in the base controller of the frames of soft bits transmitted and generation of a fourth frame of hard bits;

- generation, in the base controller, of the accuracy indicator to be transmitted in the cellular network infrastructure such that the said accuracy

SUB
A1

indicator has the best level between that of the local accuracy indicator and the one that results from an error check on the fourth frame of hard bits.

5 9. Radio network controller (12a, 15a) for exploiting macrodiversity on an uplink between a user equipment (14a) and a cellular network infrastructure comprising an active set of base nodes (13, 17) which each receive radio signals transmitted by the said user equipment, characterized in that it comprises:

10 - first means for receiving a first frame of hard bits transmitted by a base node (12a, 15a) and for receiving frames of soft bits transmitted by at least two base nodes;

10 - second means for combining the said frames of soft bits and for generating a second frame of hard bits by combination of the said received frames of soft bits.

15 10. Radio network controller (12a) according to Claim 9, characterized in that it comprises:

- third means for receiving one or more accuracy indicators, each one transmitted by a base node;

20 - fourth means for requesting, if a received accuracy indicator has a good level, a first frame of hard bits from the base node that has transmitted this accuracy indicator, and for requesting, if no accuracy indicator has the good level, frames of soft bits from at least two base nodes.

25 11. Base node (13b, 13c, 17b, 17c) for exploiting the macrodiversity on an uplink between a user equipment (14a) and a radio network controller (12a, 15a) of a cellular network infrastructure, arranged to receive radio signals transmitted by the said user equipment, characterized in that it comprises:

- first means for generating a frame of soft bits on the basis of the radio signal received by the said base node and a corresponding frame of hard bits:

30 - second means for transmitting, in the cellular network infrastructure, an accuracy indicator that results from an error check on the frame of hard bits;

- third means for transmitting the frame of hard bits and for transmitting the frames of soft bits to the radio network controller (12a, 15a).

SUB
A1

5

13. Base node (17c) according to Claim 11, characterized in that it comprises fourth means for receiving one or more accuracy indicators transmitted by another base node (17b) and for activating the said third means in order to transmit the frame of hard bits or the frames of soft bits depending on the received accuracy indicator or indicators.